

WHAT IS CLAIMED IS:

5

1. A resonance-frequency measuring method
for measuring a resonance frequency of an
information recording/reproducing device reproducing
information recorded on a medium by driving a
10 mechanism unit, the method comprising:

the measuring step of applying sine-wave
oscillations at different frequencies one by one to
said mechanism unit, and counting the number of
times information reproduced upon application of
15 each of said sine-wave oscillations differs from
information indicating an aimed location; and

the resonance-frequency determining step
of determining said resonance frequency according to
said number of times counted in said measuring step.

20

2. The resonance-frequency measuring
25 method as claimed in claim 1, wherein said measuring
step applies said sine-wave oscillations to said
mechanism unit by adding sine-wave signals at
different frequencies one by one to a control signal
controlling an actuator to drive said mechanism unit.

30

3. The resonance-frequency measuring
35 method as claimed in claim 1, wherein said
resonance-frequency determining step judges a
frequency of the sine-wave oscillation maximizing

10056865 012502

said number of times to be said resonance frequency.

5

4. The resonance-frequency measuring method as claimed in claim 2, wherein said resonance-frequency determining step judges a frequency of the sine-wave signal maximizing said number of times to be said resonance frequency.

15

5. An information recording/reproducing device comprising:

a mechanism unit causing information recorded on a medium to be tracked;

a driving unit driving said mechanism unit;

a filter removing an unnecessary component from a control signal controlling said driving unit;

measuring means for applying sine-wave oscillations at different frequencies one by one to said mechanism unit, and counting the number of times information reproduced upon application of each of said sine-wave oscillations differs from information indicating an aimed location;

resonance-frequency determining means for determining said resonance frequency according to said number of times counted by said measuring means; and

filter adjusting means for adjusting a characteristic of said filter so that said resonance frequency determined by said resonance-frequency determining means becomes a cutoff frequency of said filter.

40056865 042502

6. The information recording/reproducing device as claimed in claim 5, wherein said measuring means applies said sine-wave oscillations to said mechanism unit by adding sine-wave signals at
5 different frequencies one by one to said control signal.

10
7. The information recording/reproducing device as claimed in claim 5, wherein said resonance-frequency determining means judges a frequency of the sine-wave oscillation maximizing
15 said number of times to be said resonance frequency.

20
8. The information recording/reproducing device as claimed in claim 6, wherein said resonance-frequency determining means judges a frequency of the sine-wave signal maximizing said number of times to be said resonance frequency.

25
9. The information recording/reproducing device as claimed in claim 5, wherein said filter comprises a plurality of notch filters combined so
30 as to have a predetermined notch filter characteristic.

35

40056865.042502

10. The information recording/reproducing device as claimed in claim 9, wherein said filter comprises:

5 a first notch filter having a first cutoff frequency and exhibiting substantially symmetrical gain changes at frequencies below and above said first cutoff frequency;

10 a second notch filter having a second cutoff frequency lower than said first cutoff frequency, and exhibiting a smaller amount of gain changes and a smaller maximum gain at frequencies below said second cutoff frequency than an amount of gain changes and a maximum gain at frequencies above said second cutoff frequency; and

15 a third notch filter having a third cutoff frequency higher than said first cutoff frequency, and exhibiting a larger amount of gain changes and a larger maximum gain at frequencies below said third cutoff frequency than an amount of gain changes and
20 a maximum gain at frequencies above said third cutoff frequency.

25 11. The information recording/reproducing device as claimed in claim 10, wherein said filter further comprises a fourth notch filter having a fourth cutoff frequency lower than said second
30 cutoff frequency, and exhibiting substantially symmetrical gain changes at frequencies below and above said fourth cutoff frequency.

35

12. An electric filter comprising a

10055665.012502

plurality of notch filters combined so as to have a predetermined notch filter characteristic, the notch filters having different frequency characteristics.

5

13. The electric filter as claimed in claim 12, wherein said notch filters include:

10 a first notch filter having a first cutoff frequency and exhibiting substantially symmetrical gain changes at frequencies below and above said first cutoff frequency;

15 a second notch filter having a second cutoff frequency lower than said first cutoff frequency, and exhibiting a smaller amount of gain changes and a smaller maximum gain at frequencies below said second cutoff frequency than an amount of gain changes and a maximum gain at frequencies above
20 said second cutoff frequency; and

a third notch filter having a third cutoff frequency higher than said first cutoff frequency, and exhibiting a larger amount of gain changes and a larger maximum gain at frequencies below said third
25 cutoff frequency than an amount of gain changes and a maximum gain at frequencies above said third cutoff frequency.

30

14. The electric filter as claimed in claim 13, wherein said notch filters further include
35 a fourth notch filter having a fourth cutoff frequency lower than said second cutoff frequency, and exhibiting substantially symmetrical gain changes at frequencies below and above said fourth

10056665 042502

cutoff frequency.

40055865 012302